



INSPECTORATE

BARGE "HSM-3206"
HARDIN ST MARINE, LLC

INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T084

Table with columns for height (0 FT. to 15 FT.) and capacity (IN). Rows represent different gauge heights. Values are provided for each gauge height and capacity measurement.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/18/13

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector
INSPECTORATE AMERICA CORPORATION



INSPECTORATE

**BARGE "HSM-3206"
HARDIN ST MARINE, LLC**

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T084

Table with columns: IN, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/18/13

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-9 1/2" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3206" HARDIN ST MARINE, LLC

INNAGE TABLE

SLOP TANK PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T084

	0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.				
IN	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	0	1/4	1/2	3/4	
0	0.00	0.56	1.11	1.67	26.69	27.81	28.36	53.39	54.50	55.05	80.08	81.19	81.75	106.77	107.88	108.44	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
1	2.22	2.78	3.34	3.89	28.92	29.47	30.03	55.61	56.72	57.28	82.30	83.42	83.97	109.00	109.55	110.11	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
2	4.45	5.00	5.56	6.12	31.14	31.70	32.25	57.83	58.39	58.95	84.53	85.64	86.20	111.22	111.78	112.33	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
3	6.67	7.23	7.79	8.34	33.37	33.92	34.48	60.06	60.61	61.17	86.75	87.87	88.42	113.44	114.00	114.56	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
4	8.90	9.45	10.01	10.57	35.59	36.15	36.70	62.28	62.84	63.40	88.98	89.53	90.09	115.67	116.22	116.78	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
5	11.12	11.68	12.23	12.79	37.81	38.37	38.93	64.51	65.06	65.62	91.20	91.76	92.31	117.89	118.45	119.01	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5
6	13.35	13.90	14.46	15.01	40.04	40.60	41.15	66.73	67.29	67.84	93.42	93.98	94.54	120.12	120.67	121.23	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6
7	15.57	16.13	16.68	17.24	42.26	42.82	43.38	68.96	69.51	70.07	95.65	96.21	96.77	122.34	122.90	123.45	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
8	17.80	18.35	18.91	19.46	44.49	45.04	45.60	71.18	71.74	72.29	97.87	98.43	98.99	124.57	125.12	125.68	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
9	20.02	20.58	21.13	21.69	46.71	47.27	47.82	73.41	73.96	74.52	100.10	100.65	101.21	126.79	127.35	127.90	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
10	22.24	22.80	23.36	23.91	48.94	49.49	50.05	75.63	76.19	76.74	102.32	102.88	103.43	129.02	129.57	130.13	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
11	24.47	25.02	25.58	26.14	51.16	51.72	52.27	77.85	78.41	78.97	104.55	105.10	105.66	131.24	131.79	132.35	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 9/18/13

REFERENCE GAUGE HEIGHT : 5'-4" (RIM OF MANWAY OVER HATCH)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
INSPECTORATE AMERICA CORPORATION

