



INSPECTORATE

BARGE "HSM-3212" HARDIN ST. MARINE

INNAGE TABLE

2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T066

Table with 22 columns (0 FT. to 15 FT.) and 34 rows (0 to 34). Each cell contains numerical values representing innage measurements at various depths.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/27/12

REISSUED: 04/10/18 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-9 1/2" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



INSPECTORATE

BARGE "HSM-3212"
HARDIN ST. MARINE

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T066

Table with 21 columns (IN, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT.) and 41 rows of numerical data representing innage measurements.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/27/12

REISSUED: 04/10/18 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



INSPECTORATE

BARGE "HSM-3212"

HARDIN ST. MARINE

HULL NO. T066

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	(+) 0'- 0 1/4"
1'-0"	NIL	NIL	(+) 0'- 0 1/2"
1'-6"	NIL	NIL	(+) 0'- 0 3/4"
2'-0"	NIL	NIL	(+) 0'- 1"
2'-6"	NIL	NIL	(+) 0'- 1 1/4"
3'-0"	NIL	NIL	(+) 0'- 1 1/2"
3'-6"	NIL	NIL	(+) 0'- 1 3/4"
4'-0"	NIL	NIL	(+) 0'- 2"
4'-6"	NIL	NIL	(+) 0'- 2 1/4"
5'-0"	NIL	NIL	(+) 0'- 2 1/2"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 11/27/12

BY: 

INSPECTORATE AMERICA CORPORATION