



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with 15 columns (0 FT. to 15 FT.) and multiple rows (0 to 11) showing capacity data in barrels of 42 U.S. gallons. Each cell contains a value and a fraction (e.g., 4,870.96 0/1).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013

REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with columns for gauge height (0 FT. to 15 FT.) and rows for various measurements (0, 1/4, 1/2, 3/4). Each cell contains numerical values representing capacity or measurement data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013

REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with columns for gauge height (0 FT. to 15 FT.) and rows for barge length (0 to 11 FT.). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013

REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with 18 columns (IN, 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT., 16 FT., 17 FT.) and multiple rows of numerical data.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013
REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-3 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

2 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with columns for gauge height (IN) and distance from bow (2 FT. to 17 FT.) and rows for deck levels (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013

REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-3 3/4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with columns for gauge height (IN) and capacity (GALLONS) for various tank sections (2 FT. to 17 FT.). Each section has multiple rows for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013

REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-4" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-3216"
HARDIN ST. MARINE
OUTAGE TABLE

3 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T087

Table with columns for gauge height (IN) and capacity (GALLONS) for various barge sections (2 FT. to 17 FT.). Each section has multiple rows for different gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/05/2013

REISSUED: 04/10/2018 TO REFLECT CHANGE IN BARGE NAME

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 17'-3 1/2" (GAUGE POINT LOCATED NEAR CENTER OF TANK)
GAUGE WITH HERMETIC GAUGE TAPE ONLY.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA-CORPORATION