



INSPECTORATE

BARGE "HSM-717"
HARDIN ST MARINE, LLC

2 STAR

INNAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2200-1

Table with columns for depth (0 FT. to 9 FT.) and multiple rows of measurements for each depth, including values for IN and 1/4, 1/2, 3/4 gauges.

Table with columns for depth (10 FT. to 19 FT.) and multiple rows of measurements for each depth, including values for IN and 1/4, 1/2, 3/4 gauges.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 2/7/12

REISSUED: 12/05/17 (TO REFLECT CHANGE IN BARGE NAME)

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-2 1/2" (RIM OF 8" DIAMETER HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-717"
HARDIN ST MARINE, LLC

3 STAR

INNAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2200-1

Table with 18 columns (0 FT. to 9 FT.) and multiple rows of depth measurements and corresponding capacity values.

Table with 18 columns (10 FT. to 19 FT.) and multiple rows of depth measurements and corresponding capacity values.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 2/7/12

REISSUED: 12/05/17 (TO REFLECT CHANGE IN BARGE NAME)

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-2 1/2" (RIM OF 8" DIAMETER HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-717"

HARDIN ST MARINE, LLC

HULL NO. 2200-1

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 or 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	(+) 0' - 0 1/4"
1'-0"	NIL	(+) 0' - 0 1/2"
1'-6"	NIL	(+) 0' - 0 3/4"
2'-0"	NIL	(+) 0' - 1"
2'-6"	NIL	(+) 0' - 1 1/4"
3'-0"	NIL	(+) 0' - 1 1/2"
3'-6"	NIL	(+) 0' - 1 3/4"
4'-0"	NIL	(+) 0' - 2"
4'-6"	NIL	(+) 0' - 2 1/4"
5'-0"	NIL	(+) 0' - 2 1/2"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/05/17

BY: 
INSPECTORATE AMERICA CORPORATION