



INSPECTORATE

BARGE "HSM-719"
HARDIN ST MARINE, LLC

1 PORT

ULLAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2200-2

Table with columns for height (0 FT. to 9 FT.) and corresponding capacity values in barrels. Includes sub-rows for 1/4, 1/2, and 3/4 increments.

Table with columns for height (10 FT. to 19 FT.) and corresponding capacity values in barrels. Includes sub-rows for 1/4, 1/2, and 3/4 increments.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 2/14/12
ISSUED: 12/05/17 (TO REFLECT ULLAGE GAUGING)

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-2 1/4" (RIM OF 8" DIAMETER HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION







INSPECTORATE

BARGE "HSM-719"  
HARDIN ST MARINE, LLC

2 STAR

ULLAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2200-2

Ullage table with columns for IN (0, 1/4, 1/2, 3/4) and FT. (0 to 9). Contains capacity data for various tank heights.

Ullage table with columns for IN (0, 1/4, 1/2, 3/4) and FT. (10 to 19). Contains capacity data for various tank heights.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 2/14/12

ISSUED: 12/05/17 (TO REFLECT ULLAGE GAUGING)

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-2 1/2" (RIM OF 8" DIAMETER HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-719"
HARDIN ST MARINE, LLC

3 PORT

ULLAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2200-2

Table with 17 columns (0 FT. to 9 FT.) and multiple rows for each depth, showing ullage measurements and capacities.

Table with 17 columns (10 FT. to 19 FT.) and multiple rows for each depth, showing ullage measurements and capacities.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 2/14/12
ISSUED: 12/05/17 (TO REFLECT ULLAGE GAUGING)

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 16'-2 1/4" (RIM OF 8" DIAMETER HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "HSM-719"
HARDIN ST MARINE, LLC

3 STAR

ULLAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2200-2

Table with columns for height (0 FT. to 9 FT.) and corresponding capacity values in barrels. Includes rows for 1/4, 1/2, 3/4 increments.

Table with columns for height (10 FT. to 19 FT.) and corresponding capacity values in barrels. Includes rows for 1/4, 1/2, 3/4 increments.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 2/14/12

ISSUED: 12/05/17 (TO REFLECT ULLAGE GAUGING)

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 16'-2 1/4" (RIM OF 8" DIAMETER HATCH LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION (with signature)