

BARGE "MPC-641"
MARATHON PETROLEUM CORP.

OUTAGE TABLE

1STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2169-14

Table with columns for gauge height (0 FT. to 15 FT.) and rows for each foot (0, 1/4, 1/2, 3/4). Each cell contains a numerical value representing capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 7/18/08

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT : 15'-6 3/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name.



BARGE "MPC-641"

MARATHON PETROLEUM CORP.

HULL NO. 2169-14

CORRECTION TABLE FOR TRIM AFT.

FOR OUTAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(+) 0' - 0 1/8"	(+) 0' - 0 1/8"	NIL
1'-0"	(+) 0' - 0 1/4"	(+) 0' - 0 1/4"	NIL
1'-6"	(+) 0' - 0 3/8"	(+) 0' - 0 3/8"	NIL
2'-0"	(+) 0' - 0 1/2"	(+) 0' - 0 1/2"	NIL
2'-6"	(+) 0' - 0 5/8"	(+) 0' - 0 5/8"	NIL
3'-0"	(+) 0' - 0 3/4"	(+) 0' - 0 3/4"	NIL
3'-6"	(+) 0' - 1"	(+) 0' - 1"	NIL
4'-0"	(+) 0' - 1 1/8"	(+) 0' - 1 1/8"	NIL
4'-6"	(+) 0' - 1 1/4"	(+) 0' - 1 1/4"	NIL
5'-0"	(+) 0' - 1 3/8"	(+) 0' - 1 3/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "INNAGE" GAUGES, REVERSE SIGNS.

DATE: 7/18/08

BY:

INSPECTORATE AMERICA CORPORATION