



BARGE "MPC-901"

INSPECTORATE

MARATHON PETROLEUM CORP.

HULL NO. 2169-24

CORRECTION TABLE FOR TRIM AFT.

FOR OUTAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(+) 0' - 0 1/8"	(+) 0' - 0 1/8"	NIL
1'-0"	(+) 0' - 0 1/4"	(+) 0' - 0 1/4"	NIL
1'-6"	(+) 0' - 0 3/8"	(+) 0' - 0 3/8"	NIL
2'-0"	(+) 0' - 0 1/2"	(+) 0' - 0 1/2"	NIL
2'-6"	(+) 0' - 0 5/8"	(+) 0' - 0 5/8"	NIL
3'-0"	(+) 0' - 0 3/4"	(+) 0' - 0 3/4"	NIL
3'-6"	(+) 0' - 1"	(+) 0' - 1"	NIL
4'-0"	(+) 0' - 1 1/8"	(+) 0' - 1 1/8"	NIL
4'-6"	(+) 0' - 1 1/4"	(+) 0' - 1 1/4"	NIL
5'-0"	(+) 0' - 1 3/8"	(+) 0' - 1 3/8"	NIL

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "INNAGE" GAUGES, REVERSE SIGNS.

DATE: 11/6/08

BY:

INSPECTORATE AMERICA CORPORATION

BARGE "MPC-901" MARATHON PETROLEUM CORP.

OUTAGE TABLE

1 PORT



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2161-24

Table with columns for gauge height (0 FT. to 15 FT.) and rows for measurement points (0, 1/4, 1/2, 3/4). Values represent capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/6/08

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT: 15'-6 3/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and logo

BARGE "MPC-901" MARATHON PETROLEUM CORP.

OUTAGE TABLE

1 STAR



BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2161-24

Table with 17 columns (0 FT. to 15 FT.) and 15 rows (0 to 3/4). Each cell contains four numerical values representing measurements at different points.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/6/08

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT: 15'-6 1/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION



BARGE "MPC-901"
MARATHON PETROLEUM CORP.

OUTAGE TABLE

3 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2161-24

Table with columns for height (0 FT. to 15 FT.) and rows for gauge readings (0, 1/4, 1/2, 3/4) at each height. Values represent capacity in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 11/6/08

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT : 15'-6 3/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature
INSPECTORATE AMERICA CORPORATION

