



BARGE CHEM 1264

HULL NO: 14-2947

TANK NO. 1

INNAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGE TAPE ONLY

GAUGE HEIGHT: 16' 1 3/4"

Table with 36 columns (IN, 0 FT., IN, 1 FT., IN, 2 FT., IN, 3 FT., IN, 4 FT., IN, 5 FT., IN, 6 FT., IN, 7 FT., IN, 8 FT., IN, 9 FT., IN, 10 FT., IN, 11 FT., IN, 12 FT., IN, 13 FT., IN, 14 FT., IN, 15 FT.) and 108 rows of capacity data.

NOTE: CAPACITY TABLE APPLIES ONLY TO MANUAL INNAGES TAKEN AT THE TOP LIP OF HERMETIC VALVE.

NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. NO TRIM CORRECTIONS REQUIRED.

NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

NOTE: STRAPPED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES

OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 8/27/2015 BY: JMF

DATE COMPUTED: 8/30/2015 BY: WHF

DATE ISSUED: 8/30/2015

INTERTEK





BARGE CHEM 1264
HULL NO: 14-2947

TANK NO. 3
INNAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGE TAPE ONLY

GAUGE HEIGHT: 16' 2"

Table with 21 columns (IN 0 FT. to 15.00) and 21 rows (0 to 11). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

NOTE: CAPACITY TABLE APPLIES ONLY TO MANUAL INNAGES TAKEN AT THE TOP LIP OF HERMETIC VALVE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. NO TRIM CORRECTIONS REQUIRED.
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: STRAPPED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 8/27/2015 BY: JMF
DATE COMPUTED: 8/30/2015/2015 BY: WHF
DATE ISSUED: 8/30/2015

INTERTEK



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR HERMETIC GAUGE TAPE ONLY

Table with columns for height (IN) and diameter (2 FT. to 17 FT.) and rows for tank levels (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11). Each cell contains capacity values for different gauge heights (0, 1/4, 1/2, 3/4).

NOTE: GAUGE POINT: TO REFERENCE MARK ON HERMETIC GAUGING UNIT
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. NO TRIM CORRECTIONS REQUIRED.
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: STRAPPED AND COMPUTED IN ACCORDANCE WITH API MPM5 2.7

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 8/27/2015 BY: JMF
DATE COMPUTED: 8/30/2015 BY: WHF
DATE ISSUED: 8/30/2015

INTERTEK



CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR HERMETIC GAUGE TAPE ONLY

Table with columns for height (IN, 2 FT., 1/4, 1/2, 3/4) and capacity (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17 FT.). Each cell contains a numerical value representing capacity in barrels.

NOTE: GAUGE POINT: TO REFERENCE MARK ON HERMETIC GAUGING UNIT
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK. NO TRIM CORRECTIONS REQUIRED.
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: STRAPPED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 8/27/2015 BY: JMF
DATE COMPUTED: 8/30/2015 BY: WHF
DATE ISSUED: 8/30/2015

