



BARGE: HSM 3015

ULLAGE TRIM TABLE
MMC

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 PORT	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-3/8	- 00-3/8
2 STBD	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/4	- 00-1/4	00-3/8	- 00-3/8
3 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
3 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 PORT IS - 00-1/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 2 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11 7/8"

LENGTH BETWEEN DRAFT MARKS: 235'-06"

February 7, 2017



BARGE: HSM 3015
JEFFBOAT 16-2309

1 PORT
ULLAGE TABLE
MMC

CAPACITIES GIVEN IN WHOLE GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 15'-11 3/8"

Table with columns for depth (IN) and capacity (GALLONS) for various heights from 0 to 16 feet. Each height has three rows for different gauge points (1/4, 1/2, 3/4).

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 02/02/2017 BY: JM
DATE COMPUTED: 02/07/2017 BY: CL
DATE ISSUED: 02/07/2017

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

Signature of the certifying official



BARGE: HSM 3015
JEFFBOAT 16-2309

3 PORT
ULLAGE TABLE
MMC

CAPACITIES GIVEN IN WHOLE GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 15'-11 1/4"

Table with columns for IN, 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT., 15 FT., 16 FT. and rows for various measurements (0, 1/4, 1/2, 3/4, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11).

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 02/02/2017 BY: JM
DATE COMPUTED: 02/07/2017 BY: CL
DATE ISSUED: 02/07/2017

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

Signature



BARGE: HSM 3015
JEFFBOAT 16-2309

STBD SLOP
ULLAGE TABLE
8" HATCH

CAPACITIES GIVEN IN GALLONS

REFERENCE GAUGE HEIGHT: 6'-02 1/2"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.
0		0		0	4,840	0	3,690	0	2,540	0	1,390	0	240	0		0		0		0		0	
1/4		1/4		1/4	4,816	1/4	3,666	1/4	2,516	1/4	1,366	1/4	216	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,792	1/2	3,642	1/2	2,492	1/2	1,342	1/2	192	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,768	3/4	3,618	3/4	2,468	3/4	1,318	3/4	168	3/4		3/4		3/4		3/4		3/4	
1		1		1	4,744	1	3,594	1	2,444	1	1,294	1	144	1		1		1		1		1	
1/4		1/4		1/4	4,720	1/4	3,570	1/4	2,420	1/4	1,270	1/4	120	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,696	1/2	3,546	1/2	2,396	1/2	1,246	1/2	96	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,672	3/4	3,522	3/4	2,372	3/4	1,222	3/4	72	3/4		3/4		3/4		3/4		3/4	
2		2		2	4,648	2	3,498	2	2,348	2	1,198	2	48	2		2		2		2		2	
1/4		1/4		1/4	4,624	1/4	3,474	1/4	2,324	1/4	1,174	1/4	24	1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,600	1/2	3,450	1/2	2,300	1/2	1,150	1/2	0	1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,576	3/4	3,426	3/4	2,276	3/4	1,126	3/4		3/4		3/4		3/4		3/4		3/4	
3		3		3	4,552	3	3,402	3	2,252	3	1,102	3		3		3		3		3		3	
1/4		1/4		1/4	4,528	1/4	3,378	1/4	2,228	1/4	1,078	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,505	1/2	3,354	1/2	2,204	1/2	1,054	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,481	3/4	3,330	3/4	2,180	3/4	1,030	3/4		3/4		3/4		3/4		3/4		3/4	
4		4		4	4,457	4	3,307	4	2,156	4	1,006	4		4		4		4		4		4	
1/4		1/4		1/4	4,433	1/4	3,283	1/4	2,132	1/4	982	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,409	1/2	3,259	1/2	2,108	1/2	958	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,385	3/4	3,235	3/4	2,085	3/4	934	3/4		3/4		3/4		3/4		3/4		3/4	
5		5		5	4,361	5	3,211	5	2,061	5	910	5		5		5		5		5		5	
1/4		1/4		1/4	4,337	1/4	3,187	1/4	2,037	1/4	887	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,313	1/2	3,163	1/2	2,013	1/2	863	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,289	3/4	3,139	3/4	1,989	3/4	839	3/4		3/4		3/4		3/4		3/4		3/4	
6		6		6	4,265	6	3,115	6	1,965	6	815	6		6		6		6		6		6	
1/4		1/4		1/4	4,241	1/4	3,091	1/4	1,941	1/4	791	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,217	1/2	3,067	1/2	1,917	1/2	767	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4		3/4	4,193	3/4	3,043	3/4	1,893	3/4	743	3/4		3/4		3/4		3/4		3/4		3/4	
7		7		7	4,169	7	3,019	7	1,869	7	719	7		7		7		7		7		7	
1/4		1/4		1/4	4,145	1/4	2,995	1/4	1,845	1/4	695	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2		1/2	4,121	1/2	2,971	1/2	1,821	1/2	671	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,247	3/4	4,097	3/4	2,947	3/4	1,797	3/4	647	3/4		3/4		3/4		3/4		3/4		3/4	
8		8	5,223	8	4,073	8	2,923	8	1,773	8	623	8		8		8		8		8		8	
1/4		1/4	5,199	1/4	4,049	1/4	2,899	1/4	1,749	1/4	599	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,175	1/2	4,025	1/2	2,875	1/2	1,725	1/2	575	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,151	3/4	4,001	3/4	2,851	3/4	1,701	3/4	551	3/4		3/4		3/4		3/4		3/4		3/4	
9		9	5,127	9	3,977	9	2,827	9	1,677	9	527	9		9		9		9		9		9	
1/4		1/4	5,104	1/4	3,953	1/4	2,803	1/4	1,653	1/4	503	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	5,080	1/2	3,929	1/2	2,779	1/2	1,629	1/2	479	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	5,056	3/4	3,906	3/4	2,755	3/4	1,605	3/4	455	3/4		3/4		3/4		3/4		3/4		3/4	
10		10	5,032	10	3,882	10	2,731	10	1,581	10	431	10		10		10		10		10		10	
1/4		1/4	5,008	1/4	3,858	1/4	2,708	1/4	1,557	1/4	407	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	4,984	1/2	3,834	1/2	2,684	1/2	1,533	1/2	383	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	4,960	3/4	3,810	3/4	2,660	3/4	1,509	3/4	359	3/4		3/4		3/4		3/4		3/4		3/4	
11		11	4,936	11	3,786	11	2,636	11	1,486	11	335	11		11		11		11		11		11	
1/4		1/4	4,912	1/4	3,762	1/4	2,612	1/4	1,462	1/4	311	1/4		1/4		1/4		1/4		1/4		1/4	
1/2		1/2	4,888	1/2	3,738	1/2	2,588	1/2	1,438	1/2	288	1/2		1/2		1/2		1/2		1/2		1/2	
3/4		3/4	4,864	3/4	3,714	3/4	2,564	3/4	1,414	3/4	264	3/4		3/4		3/4		3/4		3/4		3/4	

NOTE: GAUGE POINT: TO TOP LIP OF 8" HATCH.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES
OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED: 02/02/2017 BY: JM
DATE COMPUTED: 02/07/2017 BY: CL
DATE ISSUED: 02/07/2017