



INSPECTORATE

BARGE "HSM-3210"
HARDIN ST MARINE, LLC

INNAGE TABLE

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T064

Table with columns for depth (0 FT. to 15 FT.) and corresponding capacity values in barrels. Includes sub-columns for 1/4, 1/2, and 3/4 increments.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 8/27/12

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation signature and name



INSPECTORATE

BARGE "HSM-3210"
HARDIN ST MARINE, LLC

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. T064

Table with columns for gauge height (0 FT. to 15 FT.) and rows for innage measurements (0 to 11). Includes values for 3-port and star configurations.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 8/27/12

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-9" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-9 1/4" (TO RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspectorate America Corporation logo and name